

alphaJET duo

- ✓ 2 PRINT SYSTEMS
- ✓ 1 – 16 PRINT LINES
- ✓ EXTENSIVE STANDARD FUNCTIONS
- ✓ LOWEST CONSUMPTION



With two print heads run by one controller, the alphaJET duo offers ultimate coding flexibility

Print

- up to 16 lines
- 96 Pixel
- Type height 0,8 - 30 mm
- Speed: max. 460 m/min. (5x5 Matrix)
- Text composition: automatic time and date functions, numbering (with autostop), textlist function, consecutive numbering, Barcodes, Data Matrix Codes, Logos etc.; True Type Fonts, optional customized software

Ink system

- Two separate ink systems
- Integrated solvent recovery i.e. efficient and ecological consumption figures
- 1-litre bottles for ink and solvent
- No compressed air required
- Easy to service



Interfaces

- USB
- Ethernet
- RS 232
- Network-capable
- Alarm relay
- Digital I/O Port with 8 inputs und 4 outputs
- 4-colour signal beacon
- Remote socket



Print head

- Visual ink jet monitoring through integrated stroboscopic magnifying glass
- Bending radius: at least 250 mm



Subject to
technical and
design changes.
E&OE

Technical data

Dimensions:	Control unit: 403 x 300 x 77 mm, L x W x H Printer enclosure (each): 510 x 320 x 320 mm Print head: 145 x 40 x 40 mm, L x W x H
Housing:	Stainless steel IP 65 protection class (no compressed air required)
Temperature:	+ 5° bis + 45° C, relative humidity max. 90 %, non-condensing
Error diagnosis:	Automatic diagnosis displayed in clear text
Power requirements:	Printer: 86 - 264 V ± 10 %, 50 - 60 Hz, Max. power consumption 1,0 / 0,5 A Control unit: 110 - 230 V, 50-60 Hz, Max. power consumption 0,15 / 0,3 A
Safety standard:	Ink return control; Automatic viscosity and ink level control; Remote monitoring of printing errors; Electronics and ink system are installed separately; Literally emission-free